

PAKSEAL PSA2000

Semi-Automatic Strapping Machine



Complete • End of Line • Packaging Solutions

M. J. MAILLIS UK
M. J. MAILLIS GROUP

PSA2000 Range and Technical Specification

Features

Light, Compact Design

Allows easy movement and installation in confined areas.
Four swivel castors (two lockable).

Easy Operation

Only minimal training is required. The operator simply passes the end of the strap around the pack and into the strap guide.

Back Stops

Removable and easily adjustable back stops.

Simple Adjustment

The PSA2000 can easily be adjusted to suit a range of strapping widths from 6mm – 12mm.

Safety

CE Safety Standard GS Approval.

Simple Maintenance

The simple design means that only basic maintenance is necessary.
Electrical and Mechanical components can be easily replaced.

Proven Reliability

Mechanical tension facility with proven reliability.

Energy Saving

The motor automatically cuts itself off if there is any delay between operating cycles.



Technical Specification

Strap Width	6mm – 12mm
Strapping Cycle	2 Seconds
Pack Sizes	Min 100mm(W) x 30mm(H) Max No Restriction
Machine Size	910mm (L) x 650mm (W) x 780mm (H)
Tension	15 – 45 kgs
Power Supply	230v, 50Hz
Power Consumption	0.8KVA
Net Weight	135kg
	The PSA range of strapping equipment supplied by M. J. Maillis (UK) Ltd is CE marked

After Sales Service

M J Maillis UK Ltd offers peace of mind with full after sales technical and service support from their nationwide team of engineers. We offer service agreements and scheduled maintenance contracts.

Warranty

Meeting CE Regulations this machine is backed by a comprehensive warranty which includes parts and labour.

www.maillis.co.uk

M. J. Maillis UK Ltd

Chrysalis Way, Langley Bridge, Eastwood, Nottingham NG16 3RY.

Issue No 01 (07/03) English

Tel: +44 (0) 1773 539000 Fax: +44 (0) 1773 539090

M. J. MAILLIS UK
M. J. MAILLIS GROUP

All specifications are correct at time of print, are for guidance purposes only and subject to change without prior notice.